



GRENADA RADIUS

Material	steel pipes $\varnothing$ 20 mm / steel profiles D30 $\times$ 35 mm
Connection thread	4 $\times$ G1/2"
Testing overpressure	1,3 MPa
Max. operating overpressure	1,0 MPa
Max. operating temperature	110 °C
Number of pipes	15, 19, 24, 32, 38



GRENADA RADIUS 1135 $\times$ 600

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input		Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C	paint [W]	chrome [W]	
695/450	58	5,3	2,5	1,275	302	245	157	300	200	415
695/500	66	5,7	2,7	1,275	331	269	173	300	200	465
695/600	86	6,6	3,1	1,275	389	316	203	400	300	565
695/750	75	7,9	3,6	1,275	470	382	245	500	300	715
935/450	58	7,1	3,4	1,271	396	322	207	400	300	415
935/500	66	7,7	3,6	1,271	434	353	227	400	300	465
935/600	86	8,9	4,1	1,271	510	415	266	500	400	565
935/750	75	10,6	4,9	1,271	627	510	328	600	400	715
1135/450	58	8,5	4,1	1,267	473	385	247	500	300	415
1135/500	66	9,2	4,4	1,267	518	422	271	500	400	465
1135/600	86	10,6	5,0	1,267	609	496	319	600	400	565
1135/750	75	12,7	5,9	1,267	753	613	394	700	500	715
1535/450	58	11,4	5,5	1,266	638	520	334	600	400	415
1535/500	66	12,3	5,9	1,266	700	570	367	700	500	465
1535/600	86	14,2	6,7	1,266	823	670	431	800	600	565
1535/750	75	17,0	7,9	1,266	1007	819	527	1000	700	715
1775/450	58	13,4	6,4	1,263	759	618	398	700	500	415
1775/500	66	14,5	6,9	1,263	832	678	436	800	600	465
1775/600	86	16,7	7,8	1,263	978	796	513	1000	700	565
1775/750	75	20,1	9,3	1,263	1189	968	623	1200	800	715

Thermal power measuring follows in accordance with EN 442. Chrome surface treatment reduces heating capacity by ~30 %. Accessories (page 64, 65 and 66) is not part of the radiator.

POSSIBILITY OF THE MIDDLE CONNECTION (per order)

radius middle connection standard

radius middle connection with cover

Connection options

DGRR 0695 0450... DGRR 0935 0450... DGRR 1135 0450... DGRR 1535 0450... DGRR 1775 0450...
 DGRR 0695 0500... DGRR 0935 0500... DGRR 1135 0500... DGRR 1535 0500... DGRR 1775 0500...
 DGRR 0695 0600... DGRR 0935 0600... DGRR 1135 0600... DGRR 1535 0600... DGRR 1775 0600...
 DGRR 0695 0750... DGRR 0935 0750... DGRR 1135 0750... DGRR 1535 0750... DGRR 1775 0750...

	Length [mm]	A [mm]	X [mm]
Plastic brackets (RAL 9006, 9016)	450	108-118	66-76
	500	109-119	59-69
	600	112-122	41-51
	750	126-136	67-77
Metal brackets (Other colours)	450	103-113	61-71
	500	104-114	54-64
	600	103-113	32-42
	750	121-131	62-72